


NOVEX[®]



EDUCATION

SH-45
FL-100

Biological Microscopes

Biological microscopes for education

The Novex biological microscopes FL-100 and SH-45 are perfect for students and amateur biologists alike. The excellent optical and mechanical construction of these microscopes together with their attractive prices makes them ideal to introduce students to nature sciences. With these robust microscopes you can study the cells of plants and animal tissues. Transparent specimens like wings of a mosquito, a hair, a piece of skin or a drop of water with paramecia can easily be placed between an object and cover glass and examined.

Magnification

The total magnification can be calculated from the magnification of the eyepiece multiplied by the magnification of the objective. All microscopes in this brochure are equipped with one wide field eyepiece WF 10x/18 with fixed pointer and three objectives 4x, 10x and 40x to achieve magnifications of 40x, 100x and 400x. Magnifications of 200x and 600x can be achieved using 20x and 60x objectives that are available for the FL-100, FL-100 H, SH-45 and SH-45 LED. The SH-45 and SH-45 LED can also be equipped with a 100x objective for magnifications of up to 1000x.

Numerical Aperture


The numerical aperture (N.A.) of the objective indicates the resolution. The higher the numerical aperture the better you can differentiate two points close to each other. It is essential to use a height adjustable Abbe condenser for microscopes with magnifications above 600x. This condenser is mounted below the mechanical stage and focuses the exact amount of light needed through the specimen, which results in a very detailed image.

Condenser

The FL-100 and FL-100 H are equipped with a single lens condenser N.A. 0.65 with iris diaphragm. The SH-45 and SH-45 LED are equipped with a height adjustable Abbe condenser N.A. 1.25.

Focussing

Course and fine adjustment knobs provide easy and precise focusing. In the case of the models SH-45 and SH-45 LED these knobs are coaxial, which means that they are mounted on a common axis.



FL-100 H
80.300

FL-100
80.200

135 x 175 x 365 mm
(B x D x H)

Model	Viewing Head	Eyepiece	Objective	Stage
FL-100 80.200	Mono 160mm, 45° 360° rotatable	WF10x/18	DIN achromatic 4x /0.10, 10x/0.25, S40x/0.65	100 x 120 mm optional X-Y stage
FL-100 H 80.300	Mono 160mm, 45° 360° rotatable	WF10x/18	DIN achromatic 4x /0.10, 10x/0.25, S40x/0.65	100 x 120 mm optional X-Y stage
SH-45 82.500	Mono 160mm, 45° 360° rotatable	WF10x/18	DIN achromatic 4x /0.10, 10x/0.25, S40x/0.65	120 x 120 mm with X-Y stage
SH-45 LED 82.600	Mono 160mm, 45° 360° rotatable	WF10x/18	DIN achromatic 4x /0.10, 10x/0.25, S40x/0.65	120 x 120 mm with X-Y stage

and the amateur biologist

Objective Changer and Objectives

The objective changer of the FL-100 and FL-100 H models can take three objectives. The SH-45 models have an objective changer for mounting four DIN objectives. The S40x / 0.65 objective is spring-loaded to protect the specimen from damage.



X-Y stage

For magnifications of 400x and above it is recommended to use an X-Y positioning stage that enables the user to position the specimen slowly and smoothly under the objective. The SH-45 and SH-45 LED are both supplied with a 50 x 30 mm X-Y stage on which the control knobs are horizontally positioned. The FL-100 and FL-100 H microscopes that have a plain stage and object clamps can be optionally equipped with an attachable 50 x 30 mm mechanical stage.

Illumination

Good illumination for microscopes is crucial to get a detailed image of the specimen. Too low light intensity will result in low resolution.

Depending on the application you can choose a 20 Watt Tungsten lamp, a 10 Watt halogen lamp or a microscope with a LED illumination.

With a LED illumination with a colour temperature of 4300° K no heat is developed. The microscope can be used in the field since it is equipped with rechargeable batteries. The LED version is supplied with an adapter for 230 Volt operations.

A halogen illumination with a colour temperature of 3100° K produces a high intensity light and is very close to the colour spectrum of daylight.

The FL-100 has a Tungsten lamp illumination.
The FL-100 H has a halogen illumination.
The SH-45 has an adjustable halogen illumination.
The SH-45 LED has an adjustable LED illumination.

SH-45 LED

82.600

SH-45

82.500



150 x 215 x 380 mm
(B x D x H)

Condenser	Focusing	Safety	Illumination
fixed, N.A. 0.65 with iris diaphragm, filter holder and daylight filter	fine and coarse adjustments, non coaxial ⁽¹⁾	adjustable	Tungsten lamp 230 Volt 20 Watt
fixed, N.A. 0.65 with iris diaphragm, filter holder and daylight filter	fine and coarse adjustments, non coaxial ⁽¹⁾	adjustable	Halogen lamp 12 Volt 10 Watt
height adjustable N.A.1.25 with diaphragm, filter holder and neutral density filter	fine and coarse adjustments, coaxial	fixed	Halogen lamp 12 Volt 10 Watt adjustable
height adjustable N.A.1.25 with diaphragm, filter holder and neutral density filter	fine and coarse adjustments, coaxial	fixed	LED adjustable with rechargeable batteries

(1) coarse adjustment with friction control

Accessories

Eyepiece

- 80.885** Wide Field eyepiece HWF 10x/18, suitable for users wearing spectacles
- 80.873** Wide Field eyepiece WF 15x/12
- 80.882** Wide Field eyepiece WF 20x/10
- 80.574** Eyepiece WF10/18 with adjustable lens and measuring graticule 10 mm / 100 parts
- 80.861** Photo eyepiece PH 2.5x/10

Objective

- 80.894** Achromatic DIN objective S20x N.A. 0.40 for FL-100 / FL-100 H
- 80.899** Achromatic DIN objective S60x N.A.0.85 for FL-100 / FL-100 H
- 82.894** Achromatic DIN objective S20x N.A.0.40 for SH-45 / SH-45 LED
- 82.899** Achromatic DIN objective S60x N.A.0.85 for SH-45 / SH-45 LED
- 82.900** Achromatic DIN objective S100x N.A.1.25 for SH-45 / SH-45 LED

Miscellaneous

- 80.839** Pair of eyecups, suitable for all eyepieces with \varnothing 28 mm
- 80.852** Polarisation set. Analyser fits in eyepiece and polariser fits into filter holder
- 80.853** Polarisation set. Analyser fits in eyepiece. The polariser is to be mounted into removable stage. Can be rotated over 360° with 5° resolution
- 80.810** Stage micrometer 1 mm / 100 parts
- 80.889** Spare bulb 230 Volt 20 Watt for FL-100
- 50.882** Spare halogen bulb 12 Volt 10 Watt for FL-100 H and SH-45
- 80.927** Adapter for reflex SLR camera with T2 thread. To be used with photo eyepiece
80.861T2 rings on request
- 80.973** Positioning X-Y stage, 50 x30 mm for FL-100 and FL-100H
- 80.960** Cabinet with handle and lock FL-100 and FL-100 H
- 80.961** Cabinet with lock for FL-100 and FL-100 H
- 82.960** Cabinet with handle and lock for SH-45 and SH-45 LED



euromex microscopen bv

Papenkamp 20

P.O. Box 4161, 6803 ED Arnhem

The Netherlands

T +31(0)26 323 22 11

F +31(0)26 323 28 33

info@euromex.nl

www.euromex.nl